

# TT EASY - TRANSPORT TANKS



## TT Easy

### TECHNICAL FEATURES

Mobile Diesel Refueling Unit for Diesel fuel transport and for direct machineries refueling operations on site through pump unit included. Permitted for transportation for direct consumption according to ADR 1.1.3.1 c). Now the TTE 200 and TTE 600 are ADR Approved Easy to carry and to handle, pvc transportable tanks are equipped with forklift pockets.

TTs Easy are available on following versions: 125 l, 200 l, 430 l and 600 l capacity. Made in polyethylene, tanks are complete with:

- Integrated nozzle holder;
- Filling tube with anti-foam-pipe;
- Integrated breathing valve;
- Integrated forklift pockets;
- Integrated handles;
- Pump unit with self priming, electric pump 12V DC (40 lpm) , with automatic nozzle on 4 m filling hose;
- Electric cable with clamps for battery connection;
- Cover Lid included on TTE 430 and TTE 600 versions;
- K 24 digital flow meter available on request;

**NEW VERSIONS AVAILABLE: TTE 200 ADR and TTE 600 ADR ADR APPROVED**



TTE 430



TTE 125



TTE ADR 200



TTE ADR 600



MODEL	CAPACITY (LT.)	PUMP UNIT	DIMENSIONS: (MM.)	WEIGHT (KG.)	TT EASY ON EU PALLET
TTE 125	125	12V DC—25 lpm	800 x 600 x 450	24	6
TTE ADR 200	200	12V DC—40 lpm	800 x 600 x 590	25	6
TTE 430	430	12V DC—40 lpm	1.160 x 760 x 780	63	2
TTE ADR 600	600	12V DC - 40 lpm	1.160 x 800 x 1.070	66	2